

20.0MM FROSTED MEDIUM TIR

Status	Production
Part no.	10139
Drawing no.	60424
Product type	Optic
Type	TIR
Pieces	1
Diameter	20.0
Height	9.90
Beam	Frosted Medium
Flange	Yes
Files	Customer 3D model (.igs) Customer drawing (PDF)



LEDs & Performances	Eff.	FWHM	Cd/lm	Spot	Cross-section	Files
Cree XP-G XLamp® White	82.1%	21.2	5.0			10139_cree_xpg_white_250408.ies
Cree MX-6 XLamp® White	87.4%	25.8	3.5			10139_cree_MX6_white_250408.ies
SSC Z1 White	81.0%	27.7	2.8			10139_Seoul_Z1_white_250408.ies
Osram Plus W5AM Dragon Cool White	83.9%	21.2	4.7			10139_Osram_Dragon_PLus_CoolWhite_250408.Idt 10139_Osram_Dragon_PLus_CoolWhite_250408.ies
SSC P4 Cool White	80.0%	23.8	2.5			10139_Seoul_P4_Cool_White_250408.ies
Osram SSL 80 degree Oslon Ultra White	82.5%	19.4	5.7			10139_Oslon_wht_250408.Idt 10139_Oslon_wht_250408.ies
Nichia NCSL 119-H3 Top Emitting Warm White	84.2%	19.6	6.0			10139_Nichia_119_WarmWhite_250408.ies
SSC Z5 Cool White	83.2%	20.7	5.4			10139_Seoul_Z5_white_250408.ies
LedEngin 3W White	82.3%	26.6	3.1			10139_LedEngin_3W_white_250408.ies
LedEngin 5W White	82.3%	24.6	3.4			10139_LedEngin_5W_white_250408.ies

Luminus Devices SST-50 White	82.2%	30.7	2.6			10139_Luminus_SST50_White_250408.ies
Everlight Shuen Warm White	82.4%	21.3	5.0			10139_Shuen_wwht_250408.ies
Everlight Shuen Cool White	82.4%	20.1	4.9			10139_Shuen_cwht_250408.ies
Avago Jade Cool White	87.4%	23.1	4.3			10139_Avago_Jade_cool white_250408.ies
Lumileds C Luxeon Cool White	82.0%	15.8	7.8			10139_Luxeon C_white_250408.ies
SSC P4 Version 7 Cool White	81.5%	22.4	4.3			10139_Seoul_New_P4_Pure_White_250408.ies
Cree XM-L XLamp® White	82.5%	24.1	4.1			10139_Cree_XM-L_white_31-01-11.ies
Cree XM-L - EZW Warm White	82.8%	28.3	3.0			10139_Cree_XM-L - EZW_warm white_200511.ies
Cree XP-C White	83.8%	16	8.0			10139_Cree_XP-C_white_270611.ies
Osram SSL 150 degree Oslon Neutral White	83.3%	17.2	7.4			10139_Oslon_150_neutral white_280711.ies
SSC Z5P pure white	%	20.1	6.1			10139_Z5P_pure white_290911.ies
Cree XB-D XLamp® Warm White	%	19.7	6.9			10139_CREE_XBD_160212.ies
Cree XT-E XLamp® Cool White	%	21.0	5.8			10139_CREE_XTE_160212.ies
SSC Z5M Warm White	%	20.6	5.4			10139_SeoulZ5M_warm white_250612.ies

Related Holders & LEDs	Avago Jade Cool White	Cree MX-6 White	Cree XB-D Warm White	Cree XM-L E2W Warm White	Cree XM-L XP-C White	Cree XP-G White	Cree XT-E Cool White	Everlight Shuer Cool White	Everlight Shuer Warm White	Everlight 3W White	Everlight 5W White	Engid Luxeon Cool White	Lumileds SST-50 White	Lumileds SST-50 Warm White	Nichia 19-H5 White	NCSL Plus Dragon Cool White	Osram SSL 150deg Neutral White	Osram SSL 80deg Ultra White	Osram SSL P4 Cool White	SSC P4 Version 7 White	SSC 21 White	SSC Z5 Cool White	SSC Z5M Warm White	SSC Z5P Pure White	
10148 20.0mm Circular Black																	✓								
10148-TS 20.0mm Self Adhesive (TS) Black																	✓								
10149 20.0mm Circular Clear																	✓								
10149-TS 20.0mm Self Adhesive (TS) Clear																	✓								
10150 20.0mm Circular White																	✓								
10150-TS 20.0mm Self Adhesive (TS) White																	✓								
10273 50.0mm Triple White																			✓	✓					
10276 50.0mm Triple White																	✓								
10283 50.0mm Triple White																			✓	✓					
10286 50.0mm Triple White																	✓								
10293 50.0mm Triple Black																			✓	✓					
10296 50.0mm Triple Black																	✓								
10303 50.0mm Triple Black																			✓	✓					
10306 50.0mm Circular Black																	✓								
10363 20.0mm Circular Black																			✓	✓					
10363-TS 20.0mm Self Adhesive (TS) Black																			✓	✓					
10364 20.0mm Circular White																			✓	✓					
10365 20.0mm Circular Clear																			✓	✓					
10365-TS 20.0mm Self Adhesive (TS) Clear																			✓	✓					
10566-TS 20.0mm Self Adhesive (TS) Black																			✓	✓					
10630 20.0mm Universal White																							✓		
10631 20.0mm Universal White	✓									✓					✓										
10632 20.0mm Universal White					✓			✓	✓			✓					✓	✓							✓
10634 20.0mm Universal White						✓																			
10637 20.0mm Universal White		✓																							
10650 20.0mm Universal White																							✓		
10651 20.0mm Universal White	✓									✓					✓										
10652 20.0mm Universal White					✓			✓	✓			✓					✓	✓							✓
10654 20.0mm Universal White						✓																			
10657 20.0mm Universal White		✓																							
10670 20.0mm Universal White																							✓		
10671 20.0mm Universal White	✓									✓					✓										
10672 20.0mm Universal White					✓			✓	✓			✓					✓	✓							✓
10674 20.0mm Universal White						✓																	✓		
10677 20.0mm Universal White		✓																							

10690 20.0mm Universal Black																					✓		
10691 20.0mm Universal Black	✓								✓				✓										
10692 20.0mm Universal Black				✓			✓	✓			✓				✓	✓						✓	
10694 20.0mm Universal Black					✓																		
10697 20.0mm Universal Black		✓																					
10710 20.0mm Universal Black																						✓	
10711 20.0mm Universal Black	✓												✓										
10712 20.0mm Universal Black				✓			✓	✓			✓				✓	✓						✓	
10714 20.0mm Universal Black					✓																		
10717 20.0mm Universal Black		✓																					
10730 20.0mm Universal Black																						✓	
10731 20.0mm Universal Black	✓												✓										
10732 20.0mm Universal Black			✓		✓		✓	✓	✓		✓				✓	✓						✓	
10733 20.0mm Universal Black			✓		✓		✓																
10734 20.0mm Universal Black						✓																	✓
10737 20.0mm Universal Black		✓																					
47.313.5001.80 with 47.313.-320.80 20.0mm BJB® Black																				✓	✓		

Carclo Optics endeavours to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct and up to date information, Carclo suggest using the Opticselect tool on our website <http://www.carclo-optics.com>.
Copyright © Carclo 2010

General Instruction - Optics & Holders

Handling instructions

- Do not handle or install lenses without wearing gloves, skin oils may damage the lens or the light transmission.
- Clean lenses with a mild soap and water and dry with a clean soft cloth.
- Do not use any commercial solvents on lenses.
- Mount holders with low Odour epoxies and allow time for them to out gas to stop lenses fogging.

Disclaimer - Optics & Holders

Please note that flow lines, weld lines, surface scratches and small black or white inclusions within the lenses are acceptable if the optical performance of the lens is within the specification described below:

For optics that have FWHMs of 20 degrees or less, the general tolerance is +/-2 degrees OR the tolerances stated below - whichever is the greater.

For all optics except Rippled and Frosted;

- FWHM = Datasheet Value +/-10%.

For all Rippled and Frosted Optics;

- FWHM = Datasheet Value +/-20%

For all Optics;

- Efficiency = Datasheet Value +infinity / -10%

The yellowing / browning of polycarbonate lenses and holders can occur due to the natural ageing process and exposure to heat and UV and as Carclo Optics 103 Buckingham Ave, Slough, Berkshire, SL1 4PF ENGLAND
Tel: +44 (0)1753 575011 Fax: +44 (0)1753 811359

such is not covered by Carclo's warranty.

General Instruction - Taped Holders

[Click here to view the 3M Technical Data Sheet](#)

- When assembling the pre-taped holder onto the mating surface, the application must be made straight and square, so that the tape bonds consistently with mating surface. Assembly at an angle might cause an imperfect bond to the mating surface.
- Remember to ascertain the compatibility of the different substrates with the tape, as humidity and temperature fluctuations will weaken its adhesive.
- To obtain optimum adhesion, the bonding surfaces must be clean, dry, free from grease and dirt and must be well unified.
- Some typical surface cleaning solvents are isopropyl alcohol or heptane. *
- ** If cleaning of PCB or LED surfaces is required, please follow strictly the cleaning instructions recommended by your PCB and/or LED manufacturer - this is important to note, as cleaning in some circumstances can damage LEDs or other electronic components on the PCB. Please also note that optical components should not be cleaned using any chemicals - only a micro fibre cloth should be used to remove fingerprints or other traces from handling.*
- ** Carefully read and follow the manufacturer's precautions and directions for use when working with solvents. These cleaning recommendations may not be compliant with the rules of certain Air Quality Management Districts in California; consult applicable rules before use.*

Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure and moderate heat, from 100°F (38°C) to 130°F (54°C), will assist the adhesive in developing intimate contact with the bonding surface.

Ideal tape application temperature range is 70°F to 100°F (21°C to 38°C). Initial tape application to surfaces at temperatures below 50°F (10°C) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

During assembly the optic when placed on the PCB should be firmly held for 1-5 seconds to ensure the best possible bond. The tape will reach its final strength in 72 hours, dependent on the material and ambient conditions.

We request that the customer ensures (and fully tests) the suitability and sufficiency of the bond in his product. For example, mechanical stress, vibration and holes on the surface of the circuit board can weaken the strength of the tape.

Disclaimer - Taped Holders

Shelf Life - There is 1 year expected shelf life from the date of purchase direct from Carclo.

All Carclo lenses supplied with tape use the same high strength double-coated tape (unless otherwise mentioned in the datasheet). This tape is specifically selected for this application.

These tapes generally work well together with PCBs and LEDs on the market. The customer must take the necessary measures to ensure complete compatibility with their particular application, product, PCB, LED and/or other components.

Testing and verifying of the adhesives and their combinations is the responsibility of the customer.

The customer is solely responsible for evaluating the application of double sided tape to Carclo Holders and the adhesion of double sided tape holders to determine whether such double-sided tape is fit for a particular purpose and suitable for the users method of application. The selection of double-sided tape in the adhesion of double sided tape holders is not covered by Carclo's warranty.

Carclo cannot take responsibility for the results obtained by others whose methods we cannot control. It is always the customer's responsibility to determine the adhesive's suitability for their product and to take precautions for protection of property and persons against any hazards that may be involved in the handling and use of adhesives. Carclo disclaims all warranties, including warranties of merchantability or suitability for a particular purpose, arising from use of any adhesive product. Carclo disclaims any liability for consequential or incidental damages of any kind, including lost profits.

All rights reserved. No part of this publication may be copied, reproduced in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, illustrations not to be removed, without our prior permission. Carclo Optics reserves the right to make changes at any time in order to supply the best products possible.