


◆ SPECIFICATION

DESCRIPTION	UL2896 - 30N × 80mm * 0.5p * (4/4 , 8/8) * (0.05*0.32) * P7		
KRT PART NO.		DRAWING NO.	

▶ CABLE TYPE (PATTERN : 7)

▶ CABLE DIMENSION [unit : mm]



DESCRIPTION	Abbr	Dimension	Tolerance
PITCH	P	0.5	± 0.05
NO. OF CONDUCTOR	N	30	-
CABLE LENGTH	L	80	±2.00
STRIP LENGTH	S1	4	± 1.0
	S2	4	± 1.0
S/T LENGTH	B1	8	± 2.00
	B2	8	± 2.00
INSERT THICK	T	0.3	± 0.05
WIDTH	W	15.50	± 0.10
SPAN	PA	14.50	± 0.10
MARGIN	M	0.50	± 0.10
CONDUCTOR THICK	Ct	0.05	± 0.01
CONDUCTOR WIDTH	Cw	0.32	± 0.03
LESS THAN	A	0.5	-
PLATED	PL	1 μ m ↑	

⊙ REMARK

KORA TECH CO., LTD.

Data input

STYLE	N	TL	P	S1	S2	B1	B2	Ct	Cw	pattern
UL2896	30	80	0.50	4	4	8	8	0.050	0.32	7

1. 위의 값들을 입력한다