


**TOLERANCE:**

Abbr.	TOLERANCE				
	P=0.5	P=0.8	P=1.0	P=1.25	P=2.54
P	±0.05	±0.08	±0.08	±0.10	±0.20
Pt	±0.08	±0.10	±0.10	±0.15	+0.2 -0.4
W	±0.08	±0.10	±0.10	±0.20	+0.2 -0.4
M	±0.08	±0.15	±0.15	±0.20	±0.30
Cw	±0.02	±0.03	±0.03	±0.03	±0.04
L	(30~100)±3, (101~300)±5, (301~600)±10, (Length more than 601mm)±15mm				



Tolerance of Cutting Tilt

No. of Conductor	Dimension							
	P	L	M	Cw	S1±1.0	S2±1.0	d1±2.0	d2±2.0
29	1.00	130	1	0.7	4	4	8	8

4					DATE	UNIT: mm	TITLE: FLAT FLEXIBLE CABLE (TERMINAL TYPE : T1)	瀚荃股份有限公司 CviLux Corporation	
3				DRAWN BY:		TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL: SEE PRODUCT SPECIFICATION		
2				ENGINEER:		X ±	X' ± 1'	DRAWING NO. FFC001SC FILE NO.	
1				CHECKED BY:		XX ±	X" ±		
SYN	NAME	DATE	REVISIONS	APPROVED BY:		XXX ±	XX ±	CUST. CODE:	
								SCALE 1 / 1	SHEET 1 OF 1